

M-TUBE System Premium

Lichtleiterwerkstoff	PMMA UL94
Gehäusewerkstoff	PC UL94
Lichtleiterlänge	100, 300, 500, 700 mm
Durchmesser Lichtleiter	5, 6, 8, 10 mm
Verfügbare Farben	weiß (5600K), warmweiß (3500K), rot, grün, blau
Betriebsspannung LED (typ.)	3,6V (weiß, warmweiß, grün, blau); 2,1V (rot)

Netzteil

.....

Eingangsspannung	230V AC / 50 Hz
Ausgangsspannung	12V DC / 750mA / 9W
Betriebstemperatur	-40°C ... +70°C
Schutzklasse	II
Kabellänge	ca. 1,5 m
Gewicht	ca. 500g

Treibergehäuse

.....

Betriebsspannung	11V ... 24V DC
Stromaufnahme	max. 750mA
Betriebstemperatur	-40°C ... +70°C
Schutzart	IP 44
Ausgang (max. 9V je Kanal)	6 * 100mA Konstantstrom

Technical Data

M-TUBE System Premium

Light guide material	PMMA UL94
Housing material	PC UL94
Light guide length	100, 300, 500, 700 mm
Light guide diameter	5, 6, 8, 10 mm

Available colours	white (5600K), warmwhite (3500K), red, green, and blue
Operating voltage (typ.)	3,6V (white, warmwhite, green, blue); 2,1V (red)

Power supply

.....

Input voltage	230V AC / 50 Hz
Output voltage	12V DC / 750mA / 9W
Operating temperature	-40°C ... +70°C
Protection class	II
Cable length	ca. 1,5m
Weight	ca. 500g

Terminal box

.....

Operating voltage	11V ... 24V DC
Power consumption	max. 750mA
Operating temperature	-40°C ... +70°C
IP Code	IP 44
Output (max. 9V per port)	6 * 100mA constant current